

LTE Router Multi Use

The “LTE-Router Multi Use” is a real universal genius. Equipped with LTE and WAN, it is ready for all requirements in the direction of internet communication. The router thus covers all requirements in



the field of plant communication and direct marketing.

The option of communicating with the router via Wifi simplifies installation and maintenance on site considerably. The LTE mode allows the router to be used as a fallback in case of a DSL connection failure.

Technical data

LTE-Router Multi Use

LTE Cellular router	LTE 4G / GSM/GPRS/EDGE/UMTS
LAN	1 x LAN 10/100 Mbit
WAN	1 x WAN (can be configured as LAN)
Wireless	802.11 b/g/n 2x2 mimo
Encryption	VPN-Client
Protocolls	IPSec Client/Server, VPN Client/Server, L2TP, PPTP
Working temperature range	-40°C to +75°C
Material	Metal housing
Weight	250 g
Antenna	Incl. 2 pieces magnetic base antenna for LTE
Mounting	Top hat rail adapter
Dimensions (BxHxT)* in mm	100 x 30 x 85
Compatibility (Internet access)	For all Solar-Log™ models
Compatibility (transfer to direct marketers)	For previous models Solar-Log 1000, 1200, 1900 und 2000; not needed for Solar-Log Base
Warranty	12 months
Article number	257252

*Housing measurements are presented without antenna connectors and screws